

GUIDELINES FOR SHADE SHELTERS

Shade shelters are not designed, engineered, or built to support any additional weight

Therefore, NO hammocks, swings, swing chairs, etc. are allowed to be attached to the shade shelter.

- No open flame devices may be used inside
- Washers, dryers, heaters, appliances, and A/C units are prohibited.
- No floors may be built.
- No Digging
- Shelter size may **not** be expanded with added length or width past the shelter legs. You will be asked to remove any such modifications immediately.
- No holes are to be drilled into the structure. No nails or screws may be placed into the roof rafter ends.
- All nails, screws, and coverings must be removed and disposed of before departure. Any materials left on site are subject to a \$100 clean-up and disposal fee

April 1st - October 1st: ONLY MESH WIND SCREENS are allowed. Only up to 3 sides of shelter may be covered

- No Tarps or other materials allowed April 1st – October 1st
- Winds screens may be secured with maximum size #8 screws or 8D nails.

October 1st - April 1st: Fully enclosed shelters are permitted (more than 3 sides covered)

-Wind screens are not required to be fire retardant if they are covering 3 sides or less of shelter,

ANY AMOUNT of other material covering shade shelter must be fire retardant or fireproof.

Approved Materials for Oct. 1st - Apr. 1st:

- Fire retardant Poly sheeting 6 mil minimum (clear or opaque)
- Fire retardant Poly Tarp (tan or white)
- Fire retardant Polyethylene Mesh wind screen (required only if covering more than 3 sides of shelter)

*All materials required to be fire retardant must be easily identifiable as such

IF ANY MATERIAL COVERS MORE THAN 3 SIDES OF SHELTER:

- A battery powered smoke detector must be mounted at the highest point and tested weekly
- A UL rated 2A-10BC portable fire extinguisher must be mounted inside

Electrical: Maximum combined total of 20 amps electrical power from the power pedestal-

Extension cords must be 3 prongs, UL rated for outdoor use and gauged for the appropriate amperage. Cord may not be longer than 50' and cannot be attached to the shelter by nailing or stapling. Excess of 20 amps will melt the outlets.

Electric devices:

Must not exceed the amperage rating of the protective electrical breaker (20A).

Must have clearance to combustibles recommended by the manufacturer or 36" on the front, 18" on either side, 9" from the rear and set on fireproof material.

Shelters are subject to inspection by MBTP personnel at any time.

Site # _____ Name: _____ Date: _____